

AFEplus ENERGY XL



The Active Front End is a controllable rectifier with several advantages, including the bidirectional exchange of energy between the DC and AC supply, by controlling the DC Bus voltage. With an intelligent conversion system, based on IGBT technology, the AFEplus Energy provides a power exchange with the active power line only ($\cos\Phi$ close to one) maintaining sinusoidal line currents. The Active Front End is used to return excess energy to the grid and also reduce the harmonics of the grid current.

Model @400 Vac

In @ Light Overload 120% x 30 sec.
(Arms)
In @ Standard Overload 150% x 30 sec.
(Arms)
Maximum Output Continuous Current
(kW)

AFEplus ENERGY XL		
40	48	60
47,4	54,5	68,1
42,2	48,5	60,6
33	38	47

DIMENSIONS

H - mm	322
L - mm	194
P/D - mm	253
Kg	9,6



TECHNICAL DATA SHEET | AFEplus ENERGY XL

Supply voltage	3 x 400-10% ÷ 440+10% Vac
PC programming and device interfacing	Modbus RTU RS485, Modbus TCP-IP
Fieldbus	CANbus, PROFINET/EtherCAT, Profibus
Harmonic content	Sinusoidal line current with THD \leq 3%

CERTIFICATIONS

Our AFEplus ENERGY XL converter guarantees the best performance and simple use and can be used with many of the applications sought after on the market, in compliance with approved international Standards EC (Europe).



BDF DIGITAL S.p.a.
info@bdfdigital.it | www.bdfdigital.com

VICENZA | Head Office
Via Dell'Oreficeria, 41
36100 - Vicenza (VI)
tel. +39 0444 343555

FIRENZE | CNC Division
Via di Pratigione 15/5
50019 - Sesto Fiorentino (FI)
tel. +39 055 881441

MILANO | CNC Application
Viale Fulvio Testi 128
20092 - Cinisello Balsamo (MI)
tel. 840000567-1